




Mirror HIDDEN ATM CAMERA

FEATURE & APPLICATION:

This Hidden camera series is specially designed for high level security or concealed monitoring applications such as bank, ATM machine, airport, museum, detective, spy and home security. The outlook design is a mirror built-in with hidden camera. The camera will not be noticed while it is used as a mirror for viewing the blind corner. In fact, the mirror was made from a patented high-tech material which cannot be seen through by human eyes, yet can be seen through by camera. Therefore, the hidden camera will be hardly recognized.



Front View

Side View

SPECIFICATION:

Model Number		HDC-ATS	HDC-ATH
Scanning System	NTSC	525 lines 2: 1 interlace	
	PAL	625 lines 2: 1 interlace	
Scanning Frequency	NTSC	15,734Hz(H), 60Hz(V)	
	PAL	15,625Hz(H), 50Hz(V)	
Effective Pixel	NTSC	510(H) x 492(V)	768(H) x 494(V)
	PAL	500(H) x 582(V)	752(H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.	
	PAL	1/50-100,000sec.	
Image Device	1/3" SONY Super HAD CCD		
Horizontal Resolution	420 TV lines		520 TV lines
Sensitivity	0.2Lux		
Signal to Noise	More than 48dB		
Gain Control	AGC		
White Balance	Auto 2500-9500°K		
BLC	Auto		
Gamma Correction	0.45		
SYNC System	Internal		
Lens/Focus point	3.6mm (Optional 4.3mm, 6mm)		
Video Output	1.0 Vp-p 75 Ohm		
Power Requirement	DC12V- Power Consumption: 100mA		
Operation Temp.	Working: -10~+50°C, Storage: -30~+70°C, Humidity:0~95%RH		
Dimension (mm)	90 x 48- Weight (N.W): 160g		