



Box IP Camera Catalog Made In Taiwan

YUC-H766R IR BOX CAMERA

- 1/3" Progressive Scan CMOS 2 MEGA PIXEL (1600x1200, 1280x1024, 1280x960, 1280x720, 800x592, 640x480, 320x240, 176x144) Triple streams (H.264/MPEG-4/JPEG)
- Max. 30FPS (1280x720, 800x592, 640x480, 320x240, 176x144), 25FPS (1280x960), 22FPS (1280x1024), 15FPS (1600x1200)
- Protocol: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Motion detection, I/O or schedule
- AWB - Electronic Shutter: 1/50 (1/60) ~ 1/100,000 second- 0.0LUX
- Auto iris lens Verifocal Lens 3.6~16mm- External zoom / focus adjustment
- PoE: 48V, IEEE 802.3af for option (max. 7W)
- LAN: 12V DC (max. 6W)- IP 66 Weatherproof



YUC-H766R-30 30Mtr IR
YUC-H766R-40 40Mtr IR
YUC-H766R-50 50Mtr IR

YUC-HD85P BULLET CAMERA

- 1/4" Progressive Scan CMOS sensor 1 MEGA PIXEL (HD 720P) Real Time,1280x720
- Triple streams (H.264/MPEG-4/JPEG), 4.3mm Lens, 0.5LUX
- Protocol: DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6, IEEE 802.1X, Multicast NTP PPPoE UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Intelligence Support: D-WDR, DNR, Sense-Up, Motion Detection, Mask, VBR/CBR



YUC-HA85P IR BOX CAMERA

- 1/4" Progressive Scan CMOS sensor 1 MEGA PIXEL (HD 720P) Real Time,1280x720
- Triple streams (H.264/MPEG-4/JPEG), 3.3 ~ 12 mm Lens, 0LUX
- Protocol: DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6, IEEE 802.1X, Multicast NTP PPPoE UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Intelligence Support: D-WDR, DNR, Sense-Up, Motion Detection, Mask, VBR/CBR



YUC-HS95 CUBE CAMERA

- 1.3 MEGA PIXEL (1280 x 1024) progressive scan CMOS sensor; H.264/MPEG-4/JPEG triple streams simultaneously , 4mm lens , 0.5LUX, BLC
- Motion detection, I/O or schedule
- Ethernet (10Base-T/100Base-Tx)
- Protocol: DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6, IEEE 802.1X, Multicast NTP PPPoE UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password

