



IP Dome Camera Catalog Made In Taiwan

YUC-HM96 IP DOME CAMERA

- 1/3" Progressive Scan CMOS 2 MEGA PIXEL (1600x1200, 1280x1024, 1280x960, 1280x720, 800x592, 640x480, 320x240, 176x144) Triple streams (H.264/MPEG-4/JPEG)
- Max. 30FPS (1280x720, 800x592, 640x480, 320x240, 176x144), 25FPS (1280x960), 22FPS (1280x1024), 15FPS (1600x1200)
- Protocol: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Motion detection, I/O or schedule
- AWB - Electronic Shutter: 1/50 (1/60) ~ 1/100,000 second- 0.1LUX
- PoE: 48V, IEEE 802.3af for option (max. 7W) - LAN: 12V DC (max. 6W)



YUC-HM96
YUC-HM96P-279

4mm
2.7~9mm

YUC-Hi96R IR VERIFOCAL VANDAL PROOF DOME

- 1/3" Progressive Scan CMOS 2 MEGA PIXEL (1600x1200, 1280x1024, 1280x960, 1280x720, 800x592, 640x480, 320x240, 176x144) Triple streams (H.264/MPEG-4/JPEG)
- Max. 30FPS (1280x720, 800x592, 640x480, 320x240, 176x144), 25FPS (1280x960), 22FPS (1280x1024), 15FPS (1600x1200)
- Protocol: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Motion detection, I/O or schedule
- 2.7~9mm Lens
- AWB - Electronic Shutter: 1/50 (1/60) ~ 1/100,000 second- 0LUX,
- PoE: 48V, IEEE 802.3af for option (max. 7W) - LAN: 12V DC (max. 6W)



YUC-HNi85 IP MINI DOME CAMERA

- 1/4" Progressive Scan CMOS sensor 1 MEGA PIXEL (HD 720P) Real Time, 1280x720
- Triple streams (H.264/MPEG-4/JPEG), 4.3mm Lens, 0.5LUX
- Protocol: DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6, IEEE 802.1X, Multicast NTP PPPoE UPnP forwarding, RTSP- Number of users 10 at one time
- Safety: User ID & Password
- Ethernet (10Base-T/100Base-Tx)
- Intelligence Support: D-WDR, DNR, Sense-Up, Motion Detection, Mask, VBR/CBR
- LED Ranges 5Mtr. - ICR Cut filter, 0LUX

