






Fail Safe Electric Bolt

<p>YB-100 Fail Safe Electric Bolt With Magnetic Feature Face plate: 205Lx35Wx40H(mm) Strike Plate: 90L x 25W x2H (mm) Cover Plate: 215L x 40W x 0.7H (mm) Bolt: 16mmDIA, stainless 16mm throw Quality: Aluminum panel with strongly style and Stainless steel Dual Voltage: DC12V Current Draw: Start 950Ma Standby 120mA Time:0/3/3/9sec. (optional) Signal Output: Door status sensor Fail Safe: Locked when energized Safety function: Built-in voltage spike suppressor Performance Testing: five hundred thousand times aging test Patent Designed: Low temperature Opening Mode:180 degree swinging door Suitable For: Wooden Door, Glass Door, Metal Door, Fire Proof Door. Authority Certification: CE & MA approved Net Weight:0. 80kg</p>	
<p>YB-200 Fail Safe Electric Bolt With Monitoring LED Face plate: 205Lx35Wx40H(mm) Strike Plate: 90L x 25W x2H (mm) Cover Plate: 215L x 40W x 0.7H (mm) Bolt: 16mmDIA, stainless 16mm throw Quality: Aluminum panel with strongly style and Stainless steel Dual Voltage: DC12V Current Draw: Start 950Ma Standby 120mA Time:0/2.5/5/9sec. (optional) Signal Output: Door status sensor Fail Safe: Locked when energized Safety function: Built-in voltage spike suppressor Feature Checking: five hundred thousand times checking passed Performance Testing: five hundred thousand times aging test Opening Mode:180 degree swinging door Suitable For: Wooden Door, Glass Door, Metal Door, Fire Proof Door. Authority Certification: CE & MA approved Net Weight:0. 80kg</p>	
<p>YB-300 Fail Safe Electric Bolt With Magnetic Feature Face plate: 205Lx35Wx40H(mm) Strike Plate: 90L x 25W x2H (mm) Cover Plate: 215L x 40W x 0.7H (mm) Bolt: 16mmDIA, stainless 16mm throw Quality: Aluminum panel with strongly style and Stainless steel Dual Voltage: DC12V Current Draw: Start 950Ma Standby 120mA Time:0/2.5/5/9sec. (optional) Signal Output: Door status sensor Fail Safe: Locked when energized Safety function: Double protect current, protect against damage Built-in voltage spike suppressor Performance Testing: five hundred thousand times aging test Patent Designed: low temperature Opening Mode:180 degree swinging door Suitable For: Wooden Door, Glass Door, Metal Door, Fire Proof Door. Authority Certification: CE & MA approved Net Weight:0. 80kg</p>	
<p>ABK-700 The Stainless Steel Bracket is for Fully Frameless Glass Door Suitable for model: YB100/200/300 Standard Structure: Stainless steel panel Suitable For: Fully Frameless Glass door Opening Mode: 180 degree swing double door Glass Thickness: 8~15mm Size: 205L x 58M x 46H(mm) Net Weight: 1.6kg</p>	