



WTMD CATALOG

VO-600 - 6 ZONES with Top Panel LED display

Areas with single or multiple areas showing the metal position. It can automatically adjust the sensibility from 0 to 99
Led display in the main board, no Led with four sides. Sound alarm, 8 doors can be put side by side at intervals of only 35 mm without mutual interference

Electric current:(100-240) +/- 10%VAC Power: <30 VA

Work environment : -20°~ +65°

Outer : 2220(h)*820(w)*500mm(d)- Inner : 2000*700*500mm W: :80kg



VO-2000 - 6 ZONES With Side LED Display

Single or multiple areas showing the metal position. Automatic recording of alarming times and number of people passed- 8 doors can be put side by side at intervals of only 35 mm without mutual interference, It can automatically adjust the sensibility from 0 to 99, high strength synthetic materials, in front of the door with LED

Electric current:(100-240) +/- 10%VAC Power: <30 VA

Work environment : -20°~ +65°

Outer: 2220(h)*820(w)*500mm(d)- Inner :2000* 700* 500mm, W:80kg



VO-1000A- External WTMD 6 multi-zone detecting areas

This product is an updated version of VO-1000 with high sensitivity and multiple detecting areas; there are 6 detecting areas spreading Evenly over the left-right detecting gatepost from its top to bottom

There are built-in LED indicating lights in both sides of detecting gate. The structure is in an exquisite design, with light weight and solid stand; therefore, the product can be assembled, disassembled or Moved easily.

Electric current: AC100V-240V/50HZ

Work environment : -20°~ +65°

Outer: 2120 mm*1169 mm*210 mm- Inner: 197*82*21CM- W: 43 Kg



VO-2400- 24 ZONES W-proof anti-visual blind designs

There are 8 detecting areas spreading evenly over the left, middle and right detecting gate boards respectively from its top to bottom with built-in super shining LED indicating lights; therefore, it is called a 24 positions LED display detecting, Information will be marked down on the super-large LCD front panel number of persons passed-by, times of alarm, strength of interfering signals, The special remote controller is prepared to adjust all functions, Sole detecting area can adjust its sensitivity privately, without coordination to adjust the overall sensitivity; it can be adjusted in 100 degrees within its scope; therefore, it can meet the customers demand to reject the items e.g. belt buckle, gold or silver jewelry- password protection- 3-grade audio tones adjustment

